

Type No. _____

Catalog No. _____

Job. Name _____

FluorLyter WFE Series

3-, 4-, 5- and 6-Light T5HO/T8

APPLICATIONS

- Food processing, manufacturing, cold storage, industrial, schools, beverage and bottling facilities, washdown areas, car washes

CONSTRUCTION

- Designed to minimize the retention of liquids or debris when hosed off
- Housing is constructed of fiberglass reinforced polyester
- Acrylic or optional polycarbonate diffusers resist breakage and reduce replacement and maintenance costs
- 5VA flammability rating (UL94) (f1) on housing (UL176)
- Water clear lens with frosted ends
- Poured in place gasket and stainless steel latches seal the enclosures from most hostile environments
- Captive geartray opens from either side for easy access
- Wide profile designed around T8 and T5HO lamps for long term energy savings
- Tamper-resistant stainless steel latches standard

ELECTRICAL

- T8 ballasts are 1.18 ballast factor instant start
- Rated for 25°C (6-light) & 40°C (4-light) ambient temperatures

OPTICS

- White reflector standard (min. 87%)
- Optional specular reflectors provide narrow beam distribution
- 3-, 4-, 5- and 6-lamp T5HO and T8 configurations


MOUNTING

- Mounting options for V-Hook, cable and ceiling mounting systems
- Utilizes off-the-shelf 1/2" liquid-tight fittings

WARRANTY/LISTINGS

- Wet location listed (1,300 psi hosedown)
- Published one-year limited warranty
- Patented

Tested and Certified by NSF International
UL Wet Location, IP66, IP67,
NEMA 4x, ROHS



Ordering Guide Example: WFE454EB2-8

WFE	4	54	EB	2	—	8	

Series	# Lamps	Lamp/Watts	Ballast	# Ballast	Voltage	Options
WFE =	3	32 = 32w T8	EB = Electronic Ballast	2 = (2) 2 lt	5 = 480v	See Back Page
FluorLyter	4	54 = 54w T5HO		3 = (3) 2 lt	8 = 120-277v	
Linear Fluorescent	5					
Wet Location	6					

Notes:

1. All standard units include (4) V-Hook mounting brackets, (2) V-Hooks, (12) stainless steel latches (2) 1/2" entry holes (1 at each end), acrylic lens and a white reflector.
2. All units are wet location listed, IP66, IP67, NEMA 4X, and NSF Certification.

ExceLine

1611 Clovis R. Barker Road • San Marcos, TX 78666
800.545.1326 • 512.392.5821 • Fax: 512.753.1122 • www.exceline.com

PT#: EXSP086A0812

Product information is subject to change without notice

PHILIPS

FluorLyter WFE Series

3-, 4-, 5- and 6-Light T5HO/T8

Tested and Certified by NSF International. UL Wet Location, IP66, IP67, NEMA 4x, ROHS

PHOTOMETRIC DATA

Test No. 14139

FluorLyter Wet Location


4-Light T5HO

Specular Reflector with Clear

Acrylic Drop Lens

FP54T5HO/835/C

4900 Rated Lumens



Test No. 14140

FluorLyter Wet Location


4-Light T5HO

White Reflector with Clear Acrylic

Drop Lens

FP54T5HO/835/C

4900 Rated Lumens



Test No. 14135

FluorLyter Wet Location


4-Light T8

Specular Reflector with Clear

Acrylic Drop Lens

F32WT8/835/RS

2950 Rated Lumens



Test No. 14136

FluorLyter Wet Location


4-Light T8

White Reflector with Clear Acrylic

Drop Lens

F32WT8/835/RS

2950 Rated Lumens



Test No. 14141

FluorLyter Wet Location


6-Light T5HO

Specular Reflector with Clear

Acrylic Drop Lens

FP54T5HO/835/C

4900 Rated Lumens



Test No. 14142

FluorLyter Wet Location


6-Light T5HO

White Reflector with Clear Acrylic

Drop Lens

FP54T5HO/835/C

4900 Rated Lumens



Test No. 14137

FluorLyter Wet Location


6-Light T8

Specular Reflector with Clear

Acrylic Drop Lens

F32WT8/835/RS

2950 Rated Lumens



Test No. 14138

FluorLyter Wet Location


6-Light T8

White Reflector with Clear Acrylic

Drop Lens

F32WT8/835/RS

2950 Rated Lumens



OPTIONS

835-

835 lamps (shipped separate)

841-

841 lamps (shipped separate)

F-

Fusing (must specify voltage)

MR-

Miro4 specular reflector (94%)

PL-

Polycarbonate Lens

LT-

Lens retaining tether

Emergency

Consult factory for availability

ACCESSORIES

For cable mount accessories:

GRIP5-TOGGLE (2) 5' Cable Set*

GRIP10-TOGGLE

Cable Set*

* Includes cables and required fittings

For ceiling mount bracket accessory:

WBSM

(2) Ceiling Mount Brackets

(2) 10'

Fixture cannot ship with lamps installed (shipped separately)

ExceLine

1611 Clovis R. Barker Road • San Marcos, TX 78666

800.545.1326 • 512.392.5821 • Fax: 512.753.1122 • www.exceline.com

PT#: EXSP086A0812

Product information is subject to change without notice

PHILIPS