

Type No. \_\_\_\_\_

Catalog No. \_\_\_\_\_

Job. Name \_\_\_\_\_

# Kaleidoshade

## Vaportite Decorative Series Deep Bowl Shade (Remote Ballast Only)

### APPLICATIONS

- Restaurants, Taverns or Nightclubs, Food Courts, Atriums or Plazas, Malls, Retail Outlets, Stores, Athletic Clubs and Facilities, Theatres, Arenas, Stadiums, Amusement Parks.

### CONSTRUCTION

- Spun aluminum decorative shade.
- Heat and shock resistant, prismatic glass optical chamber with neoprene gasketing.
- Corrosion resistant Duraplex II White polyester powder coated finish standard.
- Optional designer finishes available. (Consult factory)
- Shades painted both sides unless ordered otherwise.

### OPTICS

- Low glare clear prismatic glass globe.

### ELECTRICAL

- All ballasts are remote mounted Fcan only (HF provided with UL Listed enclosure).
- Porcelain spring-loaded 4KV pulse rated socket-medium base.
- Compact Fluorescent ballasts are electronic HPF >95%, <10% THD.
- PLT four pin base GX24q-3(26/32W), GX24q-4(42W).
- Starting temperature: LX(HPS)-40°F/-40°C, PMA(PS)-20°F/-30°C, HF(PLT)0°F/-18°C.
- Consult factory for lamp to ballast distances.
- All metal halide fixtures are pulse start.

### MOUNTING


- Requires 1/2" threaded conduit/stem.
- Globe threads into adaptor.
- Die-cast aluminum guard turns and locks into place.
- Tamper-proof stainless steel screws lock guard to housing.

### WARRANTY/LISTINGS

- UL 1598 listed for wet locations.
- Published one year limited warranty.


#### Ordering Guide Example: RDB70MALAGC-6

<div>RDB</div>	<div>70</div>	<div>MA</div>	<div>L</div>	<div>AG</div>	<div>C</div>	<div></div>	<div>6</div>
<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>
Prefix	Wattage	Source	Lamp	Globe	Cage	Options	Voltage
RDB	70 (ED17) <sup>1</sup> 100 (ED17) <sup>1</sup>	MA	L	AG=Amber <sup>5</sup> BG=Blue <sup>5</sup> CG=Clear G=Clear Prismatic GG=Green <sup>5</sup> LG=Lexan OG=Opal <sup>5</sup> RG=Ruby <sup>5</sup>	C		1=120 4=277 6=120/277 8=120-277
	35 (ED17) 50 (ED17) 70 (ED17) 100 (ED17) 150 (ED17)	NLX <sup>2</sup> NLX <sup>2</sup> or LX <sup>3</sup> NLX <sup>2</sup> or LX <sup>3</sup> LX <sup>3</sup> LX <sup>3</sup>					
	26 (PLT) 32 (PLT) 42 (PLT)	HF <sup>6</sup>					
	100 (A) 200 (A)	IN <sup>4</sup>					



# Kaleidoshade

## Vaportite Decorative Series Deep Bowl Shade (Remote Ballast Only)



**RBD200 SHADE**  
RLP100PMALGC-8 LUMENS: 9,000  
LAMP: 100W, Clear, EFFICIENCY:  
49.2%  
Medium Base

Type No. \_\_\_\_\_

Catalog No. \_\_\_\_\_

Job. Name \_\_\_\_\_

# Kaleidoshade

## Field-Installed Mounting Accessories (All Kaleidoshade Units are Remote Ballast)


### Kaleidoshade Accessories

Accessories are field installed. Order as separate part number.

**Decorative Wall And Pole Mount Arms  
For Remote Ballast Units.**


#### RBGNH

Wall mount gooseneck arm with maximum rise.




#### RBGNH1

Wall mount gooseneck arm with medium rise.




#### RBGNH2

Wall mount gooseneck arm with no rise.




#### RBGNV

Wall mount gooseneck arm with vertical rise.



#### RBPT3


Post top arm for mounting to 3 1/2" tenon.



\*Incandescent only

#### RBPT7

Post top arm for mounting to 2 3/8" tenon.



\*Incandescent only

### Straight Arms (Ceiling Mount)

1/2 - 14 Stem 12XX = 12" stem



1/2 - 14 Stem 24XX = 24" stem

1/2 - 14 Stem 36XX = 36" stem


1/2 - 14 Stem 48XX = 48" stem

RSWC1/2XX = 1/2" Threaded Ball Swivel with Canopy  
(XX = color code)

### Mounting Details



Wallplate mounts "over" box –  
not to the box



© 2013 Koninklijke Philips Electronics N.V. All rights reserved.  
Specifications are subject to change without notice.  
[www.philips.com/luminaires](http://www.philips.com/luminaires)

PT#: SP0117A0513

Philips Lighting Company  
200 Franklin Square Drive  
Somerset, NJ 08873  
Phone: 855-486-2216

Philips Lighting Company  
281 Hillmount Road  
Markham ON, Canada L6C 2S3  
Phone: 800-668-9008