Copper Deck (DLCG280) Specification Sheet

| Project Name: | Location: | MFG: Philips Hadco |
|---------------|--------------|--------------------|
| Fixture Type: | Catalog No.: | Qty: |



Ordering Guide

Example: DLCG280 CP

| Product Code | DLCG280 | Copper Deck |
|--------------|---------|------------------|
| Finish | CP | Copper (natural) |

Specifications

CONSTRUCTION:

Hand-formed solid copper. 3 3/4" x 2 1/4" wide Copper mounting plate.

FINISH

Natural Copper is bright polished, untreated copper. Color will age naturally to a fine dark copper patina.

PANELS/LENS/GLOBE:

Opalescent Honey Glass panel is sealed with silicone inside Copper fixture.

LAMPING:

10W maximum wedge base T-5 Xenon. Lamp is included with fixture. Xenon lamp life is approximately 10,000 hours. Higher wattages may be used only with glass panels installed.

ELECTRICAL ASSEMBLY

Wedge base socket type (T3-¼ or T5). 12 volt fixture is pre-wired with 6-ft. pigtail of 18-2 AWG, 105° C, SPT-1 wire. Low voltage quick connector, catalog #GLVC3 included for easy hook-up to the low voltage supply cable, not included. 12 Volt system requires remote transformer, not included.

INSTALLATION & MOUNTING:

Two (2) stainless tapping screws x 3/4" long supplied.

WARRANTY:

Ten-year limited warranty.

CERTIFICATIONS:

ETL Listed to U.S. safety standards for wet locations. cETL Listed to Canadian safety standards for wet locations.

Height:

4 5/8" (117mm)

Width:

3 5/8" (92mm)

Projection:

1 3/4" (44mm)

Max. Weight:

ISO 9001:2008 Registered Page 1 of 1



Note: Philips reserves the right to modify the above details to reflect changes in the cost of materials and/or production and/or design without prior notice. 100 Craftway Drive, Littlestown, PA 17340 | P: +1-717-359-7131 F: +1-717-359-9289 | http://www.hadco.com | Copyright 2013 Philips HW2