
HID (I3) Specification Sheet

Project Name:	Location:	MFG: Philips Hadco
Fixture Type:	Catalog No.:	Qty:



Ordering Guide

Example: I3 G H FL 35H E

Product Code	13	HID	
Rock Guard	G	Rock Guard	*1
Finish	H N SS	Bronze Natural Brass Stainless steel (MATTE FINISH)	
Optics	FL SP H O A HS NF	Flood Spot Horizontal No Reflector Horizontal Asymmetric Horizontal Symmetric Narrow Flood	*2 *4 *3
Wattage	35H 35T6 50H 70H 70T6 100H	35W MH 35W MH T6 50W MH 70W MH 70W MH T6 100W MH	*5 *6 *7 *8 *6 *8
Voltage	E F G H	120V 208V 240V 277V	

- *1 Rock guard is optional and available in bronze and natural brass only.
- *2 70 degrees
- *3 78°-100°
- *4 15 degrees *5 Use (O) No reflector
- *6 Use (FL, SP, HA, HS, NF) optics *7 Use (FL, SP) optics
- *8 Use (O, FL, SP) optics

Specifications

HOUSING:

Single-piece compression molded fiberglass reinforced polyester composite, factory pressure tested to ensure water will not wick or leak through. Trim ring is a compression molded polyester. Rock guard used for directional glare control made of compression molded polyester. Single-piece molded silicone U-channel gasket.

Composite is textured, pressure formed, molded-in-color.

Lamps have 15° articulation either side of vertical and 358° rotation without interruption of beam pattern. Clear convex, tempered soda-lime glass for high impact resistance. 2,200-pound live-load rated, standard walk-over lens. Optional specular aluminum spun reflector available for E17 spot (15°) or flood (70°) beam pattern.

LAMPING:

Lamp is not included. 100W maximum MH medium base PAR/R 20/30 or E17. 70W maximum T6 MH.

ELECTRICAL ASSEMBLY:

4kv rated porcelain mini-can base. Nickel-plated screw shell with center contact. Bi-pin socket type (G12) for T6 lamps, with 250° Celsius high temperature teflon coated wire leads.

T6 Metal Halide lamp uses an electronic ballast. All other HID ballasts are core and coil. Ballasts are factory pre-wired and tested, and mounted to a removable tray with quick-disconnect for easy installation.

WARRANTY:

Ten-year limited warranty.

CERTIFICATIONS:

ETL listed to U.S. safety standards for wet locations. cETL listed to Canadian safety standards for wet locations. Manufactured to ISO 9001:2008 Standards. ADA Compliant when used in concrete and flush mounted with CP3 or CPS3.

ISO 9001:2008 Registered Page 1 of 2



Note: Philips reserves the right to modify the above details to reflect changes in the cost of materials and/or production and/or design without prior notice. 100 Craftway Drive, Littlestown, PA 17340 | P: +1-717-359-7131 F: +1-717-359-9289 | http://www.hadco.com | Copyright 2013 Philips HW₂

HID (I3) Specification Sheet

Project Name:	Location:	MFG: Philips Hadco
Fixture Type:	Catalog No.:	Qty:

IP RATING:

IP67 Dust tight and sealed against direct jets of water and against prolonged effects of immersion.

Height:

11 1/2" (295mm)

Width:

9 5/8" (244mm)

Max. Weight:

10.8 lb.

ISO 9001:2008 Registered Page 2 of 2



Note: Philips reserves the right to modify the above details to reflect changes in the cost of materials and/or production and/or design without prior notice. 100 Craftway Drive, Littlestown, PA 17340 | P: +1-717-359-7131 F: +1-717-359-9289 | http://www.hadco.com | Copyright 2013 Philips HW2