Pathlight (6307 (shown with stem)) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting		
Fixture Type:	Catalog No.:		Qty:	
		Ordering Guide Example: 6307 (shown with stem) ABS		
		Product Code	6307 (shown with stem)	Pathlight
		Finish	ARD ASI BLK BRN BRZ FGN GRA IRN RBZ SRT VBZ VCP VGN VTC WBZ	Antique Brass Antique Copper Antique Red Antique Red Black Brown Bronze Forest Green Granite Ironstone Rustic Bronze Shadow Rust Verde Bronze Verde Copper Verde Vintage Copper Weathered Bronze White

Specifications

CONSTRUCTION:

Stem and ground stake NOT included on line fixtures (120 Volts). All cast aluminum construction.

FINISH:

Resilient TGIC thermoset polyester powdercoat paint is electrostatically applied to every fixture. Specially formulated for Philips Outdoor Lighting, it provides UV protection, and the highest temperature rating in the industry. In addition to the standard color choices shown, a spectrum of custom colors is available.

PANELS/LENS/GLOBE:

Set of 6 Opal Acrylic (OA) panels (standard). Contact factory for other available panel options.

LAMPING:

60W maximum A19 lamp per medium base socket. Lamp is not included. Higher wattages may be used only with glass panels installed.

ELECTRICAL ASSEMBLY:

Porcelain medium base socket. Fixture is pre-wired with 18 AWG black, white, and ground wires.

WARRANTY:

Three-year limited warranty.

CERTIFICATIONS:

ETL Listed to U.S. safety standards for wet locations. cETL Listed to Canadian safety standards for wet locations.

Height: 12 7/8" (327mm)

Width: 8" (203mm)

Max. Weight: 4.75 lb.



Copyright 2014 Koninklijke Philips N.V. (Royal Philips). All rights reserved. Specifications are subject to change without notice. Philips Lighting Company 200 Franklin Square Drive, Somerset, NJ 08873 | P: +1-855-486-2216 | www.philips.com/luminaires