
Small Fluorescent Aerial Post Mount (B55230FL) Specification Sheet

 Project Name:
 Location:
 MFG: Philips Lighting

 Fixture Type:
 Catalog No.:
 Qty:





Ordering Guide

Example: B55230FL ABS B 13W

Product Code	B55230FL	Small Fluorescent	
		Aerial Post	
		Mount	
Finish	ABS	Antique Brass	
	ACP ARD	Antique Copper Antique Red	
	ASI	Antique Red Antique Silver	
	BLK	Black	
	BRN	Brown	
	BRZ	Bronze	
	FGN	Forest Green	
	GRA	Granite	
	IRN	Ironstone	
	RBZ	Rustic Bronze	
	SRT VBZ	Shadow Rust Verde Bronze	
	VCP	Verde Copper	
	VGN	Verde Copper Verde	
	VTC	Vintage Copper	
	WBZ	Weathered	
		Bronze	
	WHT	White	
Panel/Globe	В	Opal Acrylic	
		Cylinder (only)	
Wattage/Source	13W	Fluorescent	
	4014/	13W	
	18W	Fluorescent 18W	
	26W	Fluorescent	
		26W	
	32W	Fluorescent	
		32W	
	42W	Fluorescent	
		42W	

Specifications

CONSTRUCTION:

One (1) piece cast aluminum cage. Cast aluminum post fitter slips over 3" dia. post (order separately) or tenon. Cast aluminum round top and bottom.

FINISH:

Resilient TGIC thermoset polyester powdercoat paint is electrostatically applied to every fixture. Specially formulated for Philips Outdoor Lighting, it provides UV protection, and the highest temperature rating in the industry. In addition to the standard color choices shown, a spectrum of custom colors is available.

PANELS/LENS/GLOBE:

Opal Acrylic (OA) cylinder available only.

LAMPING

42W maximum fluorescent ballast. Twist lock GX24q four (4) pin socket ballast provided. Electronic fluorescent ballast (Customer must specify wattage). 120 volt HPF supplied. (Lamp not supplied).

ELECTRICAL ASSEMBLY:

Fixture is pre-wired with 18 AWG black, white, and ground wires. Lantern will be prewired and tested. All electrical components are ETL listed.

MOUNTING

Fixture mounts to 3" dia. post or tenon.

WARRANTY:

Lifetime limited warranty.

CERTIFICATIONS:



Small Fluorescent Aerial Post Mount (B55230FL) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting
Fixture Type:	Catalog No.:	Qty:

ETL Listed to U.S. safety standards for wet locations. cETL Listed to Canadian safety standards for wet locations.

Height:

15"

Width:

8 1/4"

Max. Weight:

