


Medium Fluorescent Manor Wall Mount (B4110FL) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting
Fixture Type:	Catalog No.:	Qty:



Ordering Guide

Example: B4110FL ABS B 13W

Product Code	B4110FL	Medium Fluorescent Manor Wall Mount
Finish	ABS ACP ARD ASI BLK BRN BRZ FGN GRA IRN RBZ SRT VBZ VCP VGN VTC WBZ WHT	Antique Brass Antique Copper Antique Red Antique Silver Black Brown Bronze Forest Green Granite Ironstone Rustic Bronze Shadow Rust Verde Bronze Verde Copper Verde Vintage Copper Weathered Bronze White
Panel/Globe	B A H L	Opal Acrylic (standard) Clear Acrylic Opalescent Honey Glass White Iridescent
Wattage/Source	13W 18W 26W 32W 42W	Fluorescent 13W Fluorescent 18W Fluorescent 26W Fluorescent 32W Fluorescent 42W

Specifications

- CONSTRUCTION:**  
Cast aluminum bracket arm. Cast aluminum hex cage with cone bottom. Cast aluminum hex roof secured with thumbscrews. Cast aluminum finial attached to roof.
- FINISH:**  
Resilient TGIC thermoset polyester powdercoat paint is electrostatically applied to every fixture. Specially formulated for Philips Outdoor Lighting, it provides UV protection, and the highest temperature rating in the industry. In addition to the standard color choices shown, a spectrum of custom colors is available.
- PANELS/LENS/GLOBE:**  
Set of 6 Opal Acrylic (OA) panels (standard). More opaque or colored panels are preferred to help conceal an Energy Star or Fluorescent Lamp.
- LAMPING:**  
42W maximum fluorescent ballast. Electronic fluorescent ballast (Customer must specify wattage). Twist lock GX24q four (4) pin socket ballast provided. Lamp is not included.
- ELECTRICAL ASSEMBLY:**  
Fixture is pre-wired with 18 AWG black, white, and ground wires. Lantern will be prewired and tested. All electrical components are ETL listed.
- MOUNTING:**  
See template for dimensions & mounting instructions.
- WARRANTY:**

# Medium Fluorescent Manor Wall Mount (B4110FL) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting
Fixture Type:	Catalog No.:	Qty:

Lifetime limited warranty.

**CERTIFICATIONS:**

ETL Listed to U.S. safety standards for wet locations. cETL Listed to Canadian safety standards for wet locations.

**Height:**

19 3/4"

**Width:**

11 3/4"

**Projection:**

12 1/2"

**Top to Outlet:**

12 1/4"

**Max. Weight:**

10.5 lb.