Anchor Base Post (374-) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting	
Fixture Type:	Catalog No.:	Qty:	



Ordering Guide

Example: 374- 8 ABS B B D

Dunalizat Carla	074	A D
Product Code	374-	Anchor Base Post
11:1:14:2		
Height(s)	8	(8 ft.)
	10	(10 ft.)
Finish	ABS	Antique Brass
	ACP	Antique Copper
	ARD	Antique Red
	ASI	Antique Silver
	BLK	Black
	BRN	Brown
	BRZ	Bronze
	FGN	Forest Green
	GRA	Granite
	IRN	Ironstone
	RBZ	Rustic Bronze
	SRT	Shadow Rust
	VBZ	Verde Bronze
	VCP	Verde Copper
	VGN	Verde
	VTC	Vintage Copper
	WBZ	Weathered
		Bronze
	WHT	White
Photoeye (Optional)	В	120V
' ` ` '	С	208V - 277V
Outlet Location (Optional)	В	4" from Top of
		Base
	T	12" from Top of
		Pole
Outlet Options (Optional)	D	Standard Duplex
' ' '	G	GFI Duplex

Specifications

OUTLET:

GFI Duplex Outlet has dual-function indicator light, universal metal weatherproof cover. Weatherproof while in use. Heavy-duty all-metal construction. Lockable security cover. Meets NEC 406.9 (B). Weather resistant. Standard Duplex Outlet has universal metal weatherproof cover. Weatherproof while in use. Heavy-duty all-metal construction. Lockable security cover. Meets NEC 406.9 (B). Weather resistant.

CONSTRUCTION:

Cast aluminum anchor base. Cast aluminum removable access door. Tapered post welded to base.

FINISH

Resilient TGIC thermoset polyester powdercoat paint is electrostatically applied to every fixture. Specially formulated for Philips Outdoor Lighting, it provides UV protection, and the highest temperature rating in the industry. In addition to the standard color choices shown, a spectrum of custom colors is available.

WARRANTY:

Three-year limited warranty.

Tenon/Top:

3" O.D.

Anchor Rods:

(1) 3/4" dia. x 18" long galvanized steel

Base Dimensions:

8 5/8" dia. x 17 1/8"

Shaft:

4" to 3" Tapered

Wall Thickness:



Anchor Base Post (374-) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting
Fixture Type:	Catalog No.:	Qty:

.125"

Height: 8', 10'

Pole EPA Values

Height

Windspeed(mph)	8'	10'
80	17.8100	13.7200
110	8.8700	6.5700
130	7.8900	5.3200

