

# RLM Bracket ((DISCONTINUED) 34) Specification Sheet

Project Name: Location: MFG: Philips Lighting

Fixture Type: Catalog No.: Qty:





## **Ordering Guide**

Example: (DISCONTINUED) 34 241 ABS W

D. L. (O. I.	(DICCONITINUETEDA Desartos)		
Product Code	(DISCONTINURELDY) Bracket		
	34		
RLM Shade	241	Small	
	441	Medium	
	641	Large	
	251	Small	
	451	Medium	
	261	Small	
	461	Medium	
	271	Small	
	471	Medium	
	481	Medium	
	681	Large	
	291 491	Small Medium	
	691	Large	
	292	Small	
	492	Medium	
	692	Large	
		•	
Finish	ABS	Antique Brass	
	ACP	Antique Copper	
	ARD	Antique Red	
	ASI	Antique Silver	
	BLK	Black	
	BRN BRZ	Brown	
	FGN	Bronze Forest Green	
	GRA	Granite	
	IRN	Ironstone	
	RBZ	Rustic Bronze	
	SRT	Shadow Rust	
	VBZ	Verde Bronze	
	VCP	Verde Copper	
	VGN	Verde Coppei Verde	
	VTC	Vintage Copper	
	WBZ	Weathered	
		Bronze	
	WHT	White	
	RED	RLM Red	
Wire Guard	W	Wire Guard *1	
	N	No Wire Guard	
L	1		

<sup>\*1</sup> For 241, 441, 641 Shades Only

### **Specifications**

# CONSTRUCTION:

Cast aluminum decorative wall mounting plate. Cast aluminum decorative scroll securely welded to arm and wall plate. 1/2" Schedule 40 pipe formed aluminum arm. (All RLM Configurations visible under Specification Sheets under the Product Image.)

#### FINISH:

Resilient TGIC thermoset polyester powdercoat paint is electrostatically applied to every fixture. Specially formulated for Philips Outdoor Lighting, it provides UV protection, and the highest temperature rating in the industry. In addition to the standard color choices shown, a spectrum of custom colors is available.

#### MOUNTING:

Mounting Hardware is supplied.

#### WARRANTY:

Three-year limited warranty.



<sup>\*</sup>RLM Each RLM Shade Style has its own product page. (Search by model Shade number.)

# RLM Bracket ((DISCONTINUED) 34) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting
Fixture Type:	Catalog No.:	Qty:

#### **CERTIFICATIONS:**

ETL Listed to U.S. safety standards for wet locations. cETL Listed to Canadian safety standards for wet locations.

Height:

Width:

6" dia.

Projection:

Top to Outlet: 6 5/8"

