Medium Palermo Wall Mount (B57412FL) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting
Fixture Type:	Catalog No.:	Qty:



Ordering Guide

Example: B57412FL ABS U 26F

Product Code	B57412FL	Medium
Product Code	B5/412FL	Palermo Wall
		Mount
Finish	ABS	Antique Brass
	ACP	Antique Copper
	ARD	Antique Red
	ASI	Antique Silver
	BLK	Black
	BRN	Brown
	BRZ	Bronze
	FGN	Forest Green
	GRA	Granite
	IRN	Ironstone
	RBZ	Rustic Bronze
	SRT	Shadow Rust
	VBZ	Verde Bronze
	VCP	Verde Copper
	VGN	Verde
	VTC	Vintage Copper
	WBZ	Weathered
		Bronze
	WHT	White
Panel/Globe	U	Linen Glass
	G	Clear Glass
		Globe
	F	Frosted Glass
		Globe
	R	Thumb Print
		Globe
Wattage/Source	26F	26W
		Fluorescent
	32F	32W
		Fluorescent
	13F	13W
		Fluorescent
	18F	18W
		Fluorescent

Specifications

CONSTRUCTION:

Sand cast housing constructed from low copper alloy aluminum. Stainless steel and brass fasteners.

FINISH

Resilient TGIC thermoset polyester powdercoat paint is electrostatically applied to every fixture. Specially formulated for Philips Outdoor Lighting, it provides UV protection, and the highest temperature rating in the industry. In addition to the standard color choices shown, a spectrum of custom colors is available.

PANELS/LENS/GLOBE:

Precision designed, glass globe: linen, thumb print, frosted and clear glass available. Linen Glass Globe (U) is standard.

LAMPING:

32W maximum fluorescent ballast. Twist lock GX24q four (4) pin socket ballast provided. Electronic fluorescent ballast (Customer must specify wattage). 120 volt HPF supplied. (Lamp not supplied).

ELECTRICAL ASSEMBLY:

Fixture is pre-wired with 18 AWG black, white, and ground wires. Lantern will be prewired and tested. All electrical components are ETL listed.

MOUNTING:

See template for dimensions & mounting instructions.

WARRANTY:

Five Year Limited Warranty



Medium Palermo Wall Mount (B57412FL) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting
Fixture Type:	Catalog No.:	Qty:

CERTIFICATIONS:

ETL Listed to U.S. safety standards for wet locations. cETL Listed to Canadian safety standards for wet locations.

Height:

23"

Width: 11 3/4"

Projection:

Top to Outlet:

10

Max. Weight:

