Medium Riviera Wall Mount (B58412LED) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting
Fixture Type:	Catalog No.:	Qty:



Ordering Guide

Example: B58412LED ABS U W

	D=0.4401.ED	
Product Code	B58412LED	Medium Riviera Wall Mount
Finish	ABS	Antique Brass
	ACP	Antique Copper
	ARD	Antique Red
	ASI	Antique Silver
	BLK	Black
	BRN	Brown
	BRZ	Bronze
	FGN	Forest Green
	GRA	Granite
	IRN	Ironstone
	RBZ SRT	Rustic Bronze Shadow Rust
	VBZ	Verde Bronze
	VCP	Verde Bronze Verde Copper
	VGN	Verde Copper Verde
	VTC	Vintage Copper
	WBZ	Weathered
	WDZ	Bronze
	WHT	White
Panel/Globe	U	Linen Glass
Panel/Globe	K	Clear Seeded
	^	Glass Globe
	G	Clear Glass
	J ^G	Globe
	F	Frosted Glass
	['	Globe
1	14/	
Lamping	W	LED (3000K) -
	N	Warm
	IN	LED (4000K) - Neutral
		เพียนแลเ

Specifications

CONSTRUCTION:

Sand cast housing constructed from low copper alloy aluminum. Stainless steel and brass fasteners.

FINISH

Resilient TGIC thermoset polyester powdercoat paint is electrostatically applied to every fixture. Specially formulated for Philips Outdoor Lighting, it provides UV protection, and the highest temperature rating in the industry. In addition to the standard color choices shown, a spectrum of custom colors is available.

PANELS/LENS/GLOBE:

Precision designed, glass globe: linen, thumb print, frosted and clear glass available. Linen Glass Globe (U) is standard.

LAMPING:

22 total watts consumed; running at 700 mA. 4,000K (4K) color temperature, delivering 100 lumen per LED or 3,000K (3K) delivering 66 lumen per LED (10 LED's). Based on in-situ thermal testing and data from Philips Lumileds and Philips Advance, fixture can be expected to reach 55,000 hours (at >L70 lumen maintenance @ 25°C).

ELECTRICAL ASSEMBLY:

Smart Select™ Electronic Driver, 120-277 VAC, 50-60Hz, Auto-sensing. 6Kv Surge protection. -40°C to ±50°C Operating temperature. Fixture is pre-wired with 18 AWG black, white, and ground wires. Lantern will be prewired and tested. All electrical components are ETL listed.

MOUNTING:

See template for dimensions & mounting instructions.

WARRANTY:

Five Year Limited Warranty

CERTIFICATIONS:

ETL Listed to U.S. safety standards for wet locations. cETL Listed to Canadian safety standards for wet locations.

Height:



Medium Riviera Wall Mount (B58412LED) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting	
Fixture Type:	Catalog No.:	Otv.	
FIXIUIE I VDE:	Calaiod No.:	COIV:	

26 5/8"

Width:

11 1/4"

Projection:

Top to Outlet: 9 1/2"

Max. Weight:

