Medium Riviera Post Mount (B58430LED) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting
Fixture Type:	Catalog No.:	Qty:



Ordering Guide

Example: B58430LED ABS U W

Product Code	B58430LED	Medium Riviera Post Mount
Finish	ABS ACP ARD ASI BLK BRN BRZ FGN GRA IRN RBZ SRT VBZ VCP VGN VTC WBZ WHT	Antique Brass Antique Copper Antique Red Antique Silver Black Brown Bronze Forest Green Granite Ironstone Rustic Bronze Shadow Rust Verde Bronze Verde Copper Verde Vintage Copper Weathered Bronze White
Panel/Globe	U K G F	Linen Glass Clear Seeded Glass Clear Glass Globe Frosted Glass Globe
Lamping	W N	LED (3000K) - Warm LED (4000K) - Neutral

Specifications

CONSTRUCTION:

Sand cast housing constructed from low copper alloy aluminum. Stainless steel and brass fasteners.

FINISH:

Resilient TGIC thermoset polyester powdercoat paint is electrostatically applied to every fixture. Specially formulated for Philips Outdoor Lighting, it provides UV protection, and the highest temperature rating in the industry. In addition to the standard color choices shown, a spectrum of custom colors is available.

PANELS/LENS/GLOBE:

Precision designed, glass globe: linen, thumb print, frosted and clear glass available. Linen Glass Globe (U) is standard.

LAMPING:

22 total watts consumed; running at 700 mA. 4,000K (4K) color temperature, delivering 100 lumen per LED or 3,000K (3K) delivering 66 lumen per LED (10 LED's). Based on in-situ thermal testing and data from Philips Lumileds and Philips Advance, fixture can be expected to reach 55,000 hours (at >L70 lumen maintenance @ 25°C).

ELECTRICAL ASSEMBLY:

Smart Select™ Electronic Driver, 120-277 VAC, 50-60Hz, Auto-sensing. 6Kv Surge protection. -40°C to ±50°C Operating temperature. Fixture is pre-wired with 18 AWG black, white, and ground wires. Lantern will be prewired and tested. All electrical components are ETL listed.

MOUNTING:

See template for dimensions & mounting instructions.

WARRANTY:

Five Year Limited Warranty

CERTIFICATIONS:

ETL Listed to U.S. safety standards for wet locations. cETL Listed to Canadian safety standards for wet locations.

Height:

Page 1 of 2



Copyright 2014 Koninklijke Philips N.V. (Royal Philips). All rights reserved. Specifications are subject to change without notice. Philips Lighting Company 200 Franklin Square Drive, Somerset, NJ 08873 | P: +1-855-486-2216 | www.philips.com/luminaires

Medium Riviera Post Mount (B58430LED) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting
Fixture Type:	Catalog No.:	Qty:

27 3/8"

Width: 11 1/4"

Projection:

Top to Outlet:

Max. Weight:



Copyright 2014 Koninklijke Philips N.V. (Royal Philips). All rights reserved. Specifications are subject to change without notice. Philips Lighting Company 200 Franklin Square Drive, Somerset, NJ 08873 | P: +1-855-486-2216 | www.philips.com/luminaires