

# Medium Riviera Pier Mount (B58460FL) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting
Fixture Type:	Catalog No.:	Qty:



## Ordering Guide

Example: B58460FL ABS U 26F

<b>Product Code</b>	B58460FL	Medium Riviera Pier Mount
<b>Finish</b>	ABS ACP ARD ASI BLK BRN BRZ FGN GRA IRN RBZ SRT VBZ VCP VGN VTC WBZ WHT	Antique Brass Antique Copper Antique Red Antique Silver Black Brown Bronze Forest Green Granite Ironstone Rustic Bronze Shadow Rust Verde Bronze Verde Copper Verde Vintage Copper Weathered Bronze White
<b>Panel/Globe</b>	U K G F	Linen Glass Clear Seeded Glass Globe Clear Glass Globe Frosted Glass Globe
<b>Wattage/Source</b>	26F 32F 13F 18F	26W Fluorescent 32W Fluorescent 13W Fluorescent 18W Fluorescent

## Specifications

### CONSTRUCTION:

Sand cast housing constructed from low copper alloy aluminum. Stainless steel and brass fasteners.

### FINISH:

Resilient TGIC thermoset polyester powdercoat paint is electrostatically applied to every fixture. Specially formulated for Philips Outdoor Lighting, it provides UV protection, and the highest temperature rating in the industry. In addition to the standard color choices shown, a spectrum of custom colors is available.

### PANELS/LENS/GLOBE:

Precision designed, glass globe: linen, thumb print, frosted and clear glass available. Linen Glass Globe (U) is standard.

### LAMPING:

32W maximum fluorescent ballast. Twist lock GX24q four (4) pin socket ballast provided. Electronic fluorescent ballast (Customer must specify wattage). 120 volt HPF supplied. (Lamp not supplied).

### ELECTRICAL ASSEMBLY:

Fixture is pre-wired with 18 AWG black, white, and ground wires. Lantern will be prewired and tested. All electrical components are ETL listed.

### MOUNTING:

See template for dimensions & mounting instructions.

### WARRANTY:

Five Year Limited Warranty

## Medium Riviera Pier Mount (B58460FL) Specification Sheet

Project Name:	Location:	MFG: Philips Lighting
Fixture Type:	Catalog No.:	Qty:

**CERTIFICATIONS:**

ETL Listed to U.S. safety standards for wet locations. cETL Listed to Canadian safety standards for wet locations.

**Height:**

22 5/8"

**Width:**

11 1/4"

**Projection:****Top to Outlet:****Max. Weight:**