

Voice



Recessed

2'x2'

1 TT5 (25W)




mesoOptics®



airwave™



RESPONSE®



Project Name

Spec Type

Notes

Order Guide

Some combinations of product options may not be available. Consult factory for assistance with your specification.

9822

B125

Product Series & Size

Voice 2'x2'

Version

- D1** Standard T-Grid
- D2** Slot T-Grid
- A1** Air Return on Standard T-Grid
- A2** Air Return on Slot T-Grid

See details on next page

Configuration

- ST** Standalone
- CR** Continuous Row

Lamping

1 TT5 (25W)

Housing

- S** Standard (22ga.)
- C** Chicago Plenum

Wiring

- 1** 1 cct
- 7** 1 cct Dimming

Consult website for complete list of standard wiring options

Voltage

- 1** 120V
- 2** 277V
- 3** 347V

Ballast

E Standard Ballast

Consult website for ballast manufacturer information

Upgrades & Accessories

Please indicate with check mark.


☐ Lamps Included

☐ Lamps Included & Installed

☐ Job Pack


☐ Flex Whip

☐ Drywall Kit



Not available in continuous row

Can be mounted to wood frame or with hanger wire



Wood Frame




Hanger Wire


☐ Response Daylight

For details visit www.ledalite.com/response

Cross Section



Side View




Voice

Recessed

2'x2'

1 TT5 (25W)



Photometry

Report Summary


Report # 9901531
Filename 9822D1B125.ies
Efficiency 75.8%

Spacing Criteria 1.26 @ 0° along
1.46 @ 90° across

Meets RP-1-04 recommendations for VDT-Normal spaces

Candela Distribution

Vertical Angle	Horizontal Angle					Zonal Lumens
	0	22.5	45	67.5	90	
0	740	740	740	740	740	
5	737	740	747	752	757	73
15	719	737	779	814	837	221
25	673	712	789	861	882	361
35	583	625	678	736	738	417
45	438	452	460	497	475	359
55	296	295	290	309	304	268
65	173	176	167	185	179	174
75	72	73	67	81	76	80
85	14	16	15	19	17	19
90	0	0	0	0	0	



Coefficients of Utilization (%)

Ceiling: Wall:	80				70				50				0			
	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
0 RCR	90	90	90	90	88	88	88	84	84	84	84	84	76			
1	83	80	77	75	81	78	76	75	73	71	65					
2	76	71	66	62	75	69	65	67	63	60	56					
3	70	63	57	53	68	62	57	60	55	51	48					
4	65	56	50	45	63	55	50	53	48	44	42					
5	60	51	44	40	58	50	44	48	43	39	37					
6	55	46	39	35	54	45	39	44	38	34	32					
7	51	42	35	31	50	41	35	40	34	31	29					
8	48	38	32	28	47	38	32	37	31	27	26					
9	45	35	29	25	44	35	29	34	28	25	23					
10	42	32	26	23	41	32	26	31	26	22	21					

Based on a floor reflectance of 0.2

Avg. Luminance (cd/m²)


Vertical Angle	Horizontal Angle		
	0	45	90
55	1686	1651	1731
65	1337	1291	1383
75	909	846	959
85	525	562	637

IES files for this and other photometric options can be downloaded online at www.ledalite.com

Additional Information


Mounting

Integrates with most common T-bar ceiling types.



D1 Standard T-Grid

Option D1 works with 9/16" and 15/16" flat T-grid ceilings. It can also be used with slot T-grid ceilings, but it will not sit flush with the bottom of the T-bar.




D2 Slot T-Grid


Option D2 is designed to sit flush with slot T-grid ceilings and some tegular tile ceiling types.

Ceiling Types

Integrated mounting tabs can be field-adjusted to various T-bar ceiling heights for fastening directly to the T-bar grid and/or tied-off to the building structure.



Air Return



The air return version features slotted vents along the sides of the fixture. As a result, the installation method of the air return version is different to the standard version, and the fixture cannot be installed in continuous rows.

Specifications

Due to continuing product improvements, Ledalite reserves the right to change specifications without notice.

Housing

Die-formed, post-painted, 22 gauge cold-rolled steel (New York City version is 20 gauge). Wire entrances are positioned on the side of the housing to allow easy wiring access for the installer. Multiple wire entrances are available on top or side to allow continuous row mounting of fixtures. Optional frame restraint is available to provide additional support to the optical frame.

Weight

Maximum 23 lbs.

Optical System

The optical frame assembly consists of flat acrylic panels with a layer of protected MesoOptics® film that provides high-angle glare control and high efficiency. The panels are secured to a perforated center shield using a linear prismatic acrylic diffuser. The optical frame ends are constructed from die-formed cold-rolled steel assembled together with extruded aluminum profiles in a sturdy frame. The frame is hinged to allow easy access to the inside of the fixture. Maintenance can be performed from below the ceiling without tools. No hardware is visible.

Mounting

Fixture is compatible with most ceiling types. Integrated bend-out tabs are provided for different T-grid heights. Optional drywall kit is available for non-accessible ceilings. Use screws or hanger wire (supplied by others) to secure fixture.

Ballast

Electronic. Supplied with pre-installed ballast disconnects as per national electric codes.

Wiring

Optional flex whips are supplied in 6' lengths for 1x4, 2x2 and 2x4 fixtures. Flex connectors are supplied in 9' lengths for standard master/satellite configurations.

Air Return

Air return option available in 2'x2' and 2'x4' sizes only. Side rails are finished in black.

Approvals

Certified to UL & CSA Standards.
City of Chicago Approved CCEA (housing option C).
Designed to comply with NYC code requirements (Housing Option N).

Finish

Housing and Frame: Post-painted, high quality powder coat. Available in white only.