



## Ordering Information

Catalog No.	Finish	Mounting	Compatibility
26890WH	Matte White	Compatible with drywall or T-Bar ceiling types.	ProSpec track luminaires, 500W Max. NOT FOR USE
26890BK	Matte Black	Accommodates ceiling thicknesses of 1/2" to 3/4".	with ProSpec PAR56 or PAR64 track mounted units.

## Features

- ProSpec Track Strip:** Structural aluminum extrusion; average wall thickness 0.08". Adjustable to ensure that the track is always flush with the ceiling.
- Canopy:** Steel low-profile (.12") canopy to accommodate ceiling imperfections.
- Insulated Liner:** 0.040 wall high temperature extruded thermoplastic.
- Conductors:** "U" shaped copper conductor; increases contact surface and minimizes contact resistance; provides reliable positive connection.
- Mounting Brackets:** 18 ga. galvanized steel. Adjustable to accommodate 1/2" to 3/4" ceiling thicknesses.
- Knockouts:** Allows power feed from above using 3/8" or 1/2" (trade size) connector (by others).

## Finish

All painted finishes are baked enamel.

## Electrical

(2) circuits. Each circuit is 120V, 60 Hz. Each circuit has dedicated neutral for maximum control flexibility. Track is continuously grounded throughout. Electrical conductors are concealed in an insulated liner in the track. Intended for wiring to branch circuit building wire with ground, in accordance with national and local codes.

## Labels

cULus

## Job Information

## Type:

**Job Name:**

**Cat. No.:**

**Lamp(s):**

**Notes:**

Lightolier a Genlyte company

www.lightolier.com

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

© 2005 Genlyte Group LLC • 0505