



Catalog No.	Finish	Lamps	Length	Width (extension)	Height
5404WHU	White	(2) 32W T8 Fluorescent	48 3/4"	6 7/16"	3"
5404PCU	Polished Chrome				
5404PBU	Polished Brass				

Features

- End Caps:** Die-cast aluminum alloy.
- Luminous Strip:** White translucent acrylic.
- Mounting Plate:** Die Formed, 18 ga. steel.
- Junction Box Cover:** (Removable) for use with 4" or 3 1/2" octagonal junction box. Not required for horizontally mounted switchbox. Semi-gloss white.
- Diffuser:** One-Piece, translucent white 100% virgin acrylic.

Fixtures are rated for connection to 60°C building wire. Therefore, they can be used for either old or new construction.

Electrical

Ballast: Rapid Start,	Electronic 120V
Total Input Watts	69
Max.Line Current (Amps)	0.58
Power Factor	.98
Ballast Factor	0.98
THD	<10%
Min. Starting Temp.	50°

Mounting

Horizontally to wall using six 7/32" diameter mounting holes.

Note: Fixture is intended for horizontal mounting only.

Finish

All painted surfaces, baked enamel.

Labels

UL Listed, suitable for Damp Locations.

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

Lightolier a Genlyte Thomas Company

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

© 2002 Genlyte Thomas Group LLC (Lightolier Division) • A0902

www.lightolier.com

LIGHTOLIER®