

Ordering Information

Catalog No.	Lamps	Length	Width	Extension
6348N	2 Lt - 60W A-19	12 1/8"	4 7/8"	4 1/2"

Features

- 1. Glass Diffuser: Blown pure white opal glass, casts well-diffused general lighting
- Fitter: Die-formed aluminum, 16 ga. White finish. Will fit 3 1/4", 4" octagon or gem outlet box. For wall mounting only.
- 3. Cam-Lock Locking Lever/Back Plate: Concealed behind diffuser. Rotates 90° with fingertip pressure to lock glass securely in place, assures ease of relamping and maintenance. Rust proof aluminum back plate.

Electrical

No. 18 105°C thermoplastic wire. Porcelain socket-medium base. Fixture required 90°C rated supply wiring.

Labels

cULus (Suitable for Damp Locations), I.B.E.W.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte Thomas Company www.lightolier.com 631 Airport Road, Fall River, MA 02720 ◆ (508) 679-8131 ◆ Fax (508) 674-4710 We reserve the right to change details of design, materials and finish. © 2011 Genlyte Thomas Group LLC (Lightolier Division) ◆ B1111