



Catalog No.	Length	Mounting	Finishes	Use With PowerJack	Lamps (Not Included)
8632AL	6' Field Cuttable	To all Power Jacks	Brushed AL	Track 8610WH, BK Track 8611WH, BK Track 8610EWH, BK Track 8611EWH, BK Remodeler 8612EWH, BK Recessed 8613WH, BK Points 8605WH, BK Remote Transformers 8608, 8609	12V 20W, 35W T4 Bi-Pin Base GY 6.35 (Tungsten-Halogen) Lightolier No. 56361 35W Lightolier No. 56360 20W

Features

- Male Connector**
- Locking Screw-In Plug**
- Splicing/Wiring Chamber:** Brushed Aluminum.
- Metallic Braided Cable:** 6' Field cuttable.
- Die-Cast Aluminum Husk:** With circular brim for support of shade.
Brushed Finish.
- Glass Lamp Guard:** Satin finish, for effective light diffusion.
- Wire Nuts**
- Socket Base**
- Bi-Pin Round Socket**
- Spring**
- Heat Vents**
- Fuse/Fuse Holder:** 5 AMP replaceable.

Electrical

Bi-Pin ceramic socket, 6.35mm pin spacing (see lamp above). Pre-wired with 18AWG electrical cable, and covered with braided cable. Braided cable serves as one of the circuits conductors.

Finish

Brushed Metallic.

Labels

UL; CUL.

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

Lightolier a Genlyte company

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

© 2006 Genlyte Group LLC • A0206

www.lightolier.com

LIGHTOLIER®