


**Ceiling Cutout: 5 1/16" (129 mm) Dia.**

Reflector Trim		Frame-In Kit		
<b>C4MRL CLW</b>	Specular Clear, White Flange	Non-IC 120V/277V	Non-IC AirSeal® 120V/277V	IC AirSeal® 120V
<b>C4MRL CLP</b>	Specular Clear, Polished Flange	<b>C4LVMU</b> Magnetic 120/277V <b>C4LVE1</b> Electronic 120V	<b>C4LVMU</b> Magnetic 120/277V <b>C4ALVE1</b> Electronic 120V	<b>C4AICLVM1</b> Magnetic 120V <b>C4AICLVE1</b> Electronic 120V
<b>C4MRL</b> 	Add suffix. See options for other finishes.	<b>C4LVE2</b> 42-75W MR16(12V)	42-75W MR16(12V)	20-50W MR16(12V)
		<b>Remodel Frame-In Kit</b>		
		Non-IC 120V		
		<b>C4LVE1RM</b> 50W Max. MR16 (12V)		
		See C4LVE1RM specification sheet for more information.		

**Note:** Magnetic transformers may produce audible sound when used with dimmers, which may be objectionable in acoustically critical areas.

## Features

- Aperture Cone:** 16 ga. aluminum, 50° visual cutoff to lamp and lamp image. Keyed to kick reflector to prevent incorrect installation of cone. Hinged, and snaps onto kick reflector for easy tool-less installation. Available with painted white or polished flange. Interchangeable with other Evolution 4 1/2" low voltage trims.
- Kick Reflector:** 16 ga. aluminum. Specular kick reflector with directional spread lens distributes light smoothly for vertical surface wall washing.
- Directional Spread Lens:** High temperature, tempered glass. Precisely contoured to fit onto cone; replaceable.
- Socket Harness:** Porcelain bi-pin socket. Pre-wired with No. 18 PTFE leads.
- Power Harness:** Provides power to transformer.
- Frame-In Kit:** Compatible frame-in kits are listed above. See separate frame-in kit specification sheets for details.  
Non-IC and Non-IC AirSeal® - Insulation must be kept 3" away from fixture sides and wiring compartments and must not be placed above fixture in a manner which will entrap heat.  
IC-AirSeal® - Fixture may be in direct contact with insulation.
- Maximum Ceiling Thickness:** .875", 1.75" with C4TCA2 accessory (see C4TCA2 specification sheet for details.)

## Options and Accessories

### Reflector Finishes¹

Clear: CL Gold: GD White: WH Black: BK  
Comfort Clear Diffuse: CCD Champagne Bronze: CCZ

¹Specify desired flange

**W** White, **P** Polished

### Labels

CULUS Listed (suitable for wet locations), I.B.E.W.

## Job Information

## Type:


**Job Name:**

**Cat. No.:**

**Lamp(s):**

**Notes:**


**Lighting Data**



EXAMPLE: With multiple units located 2' from wall and 2' on center, the illumination on the wall 3' down from the ceiling is 24 f.c. beneath and 23 f.c. between fixtures.

**Candlepower Curve**

73W MR16 RL



Report 0825FR  
Efficiency = 47.8%

**Footcandles on Wall From Multiple Units - 73W MR16 FL**

Units 2 Feet From Wall

		← 2' →		← 3' →	
	10	8	10	9	3
1'	21	18	21	16	11
2'	24	23	24	18	13
3'	23	22	23	16	14
4'	19	19	19	14	12
5'	15	15	15	11	10
6'	12	12	12	9	8
7'	10	10	10	7	7
8'	8	8	8	6	6
9'					

Units 3 Feet From Wall

		← 2' →		← 3' →	
	2	2	2	2	1
1'	7	6	7	6	4
2'	9	8	9	8	6
3'	11	10	11	9	7
4'	11	10	11	9	7
5'	10	10	10	8	7
6'	9	9	9	7	7
7'	8	8	8	7	6
8'	7	7	7	6	6
9'					

**Job Information**

**Type:**