


## Calculite Evolution 4 1/2", Non-IC Low Voltage, Remodeler Frame-In Kit

Page 1 of 1

|           |               |        |
|-----------|---------------|--------|
| Project:  | Catalog No:   | Mfg:   |
| Location: | Fixture Type: | Qty:   |
| Notes:    |               | Lamps: |



Ceiling Cutout: 5 1/16" (129 mm) Dia.

### Ordering guide

example: C4LVE1RM + C4MRD

| Frame-In Kit    | Reflector Trim                        |                                       |                                       |                                       |                                       |                                       |  |  |                                       |
|-----------------|---------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|--|--|---------------------------------------|
| Remodeler       | Open Downlight                        | Adjustable Accent                     | Adjustable Accent                     | Adjustable 2" Aperture                | Adjustable 1 1/4" Pinhole             | Lensed Wall Washer                    | Glasslite Downlight                    | Glasslyte Adjustable                   | Lensed Adjustable                     |
| <b>C4LVE1RM</b> | <b>C4MRD</b><br>20W-50W<br>MR16 (12V) | <b>C4MRA</b><br>20W-50W<br>MR16 (12V) | <b>C4ARA</b><br>20W-50W<br>AR70 (12V) | <b>C4MR2</b><br>20W-50W<br>MR16 (12V) | <b>C4MRP</b><br>20W-50W<br>MR16 (12V) | <b>C4MRL</b><br>20W-50W<br>MR16 (12V) | <b>C4MRGD</b><br>20W-50W<br>MR16 (12V) | <b>C4MRGA</b><br>20W-50W<br>MR16 (12V) | <b>C4MRW</b><br>20W-50W<br>MR16 (12V) |

**Note:** Magnetic transformers may produce audible sound when used with dimmers, which may be objectionable in acoustically critical areas.

### Features

- Housing:** Hydroformed aluminum, 0.04" (18 ga.). Removable for access to **J-Box and transformer.**
- Mounting Frame:** Die-formed steel, 0.03" (22 ga.) galvanized steel. Accommodates existing ceilings up to 2" thick.
- Locking Clips:** Quick-Lock clips provide ratcheting coarse adjustment for ceiling thickness from 1/2" to 2" thick.
- Fine Adjustment Screws:** Provide pressure to clamp the ceiling material for secure mounting.
- Retaining Springs:** Precision-tooled steel springs secure reflector trim to housing for quick, tool-less installation.
- Quick Electrical Connector:** Keyed to accept plug from reflector trim.
- Junction Box:** 0.03" (22 ga.) galvanized steel. UL listed for 90°C supply connection. Cable clamp permit attachment of #14 or #12 ga. non-metallic cable without tools or additional connectors.
- Transformer:** Electronic, 120V 60 Hz, primary, nominal 12V secondary, short circuit and thermal protection, high power factor, THD<10%, dimmable, FCC approved, quiet operation.
- Thermal Protector:** Meets NEC and UL requirements. Insulation must be kept 3" away from fixture sides and wiring compartments and must not be placed above fixture in a manner which will entrap heat.
- Reflector Trim:** Compatible reflector trims are listed above. See separate reflector trim specification sheets for complete catalog numbers, finish, and details.

**Notes:** Vertical aiming for MR16 adjustable trims is 35° max. when used with remodeler. Vertical aiming for AR70 adjustable trims is 25° max. when used with remodeler.

### Electrical/Dimming

Dimming controls: Use with dimmers specially designed for use with electronic transformers, like Lightolier Sunrise™, Multiset™, Momentum QE series. For additional information, see Lightolier Controls Catalog or contact Lightolier Controls at 800-526-2731 or visit website at [www.lolcontrols.com](http://www.lolcontrols.com).

### Labels

CULUS Listed (suitable for damp locations), I.B.E.W.