
E7 Series


Commercial Grade Emergency Lighting

Page 1 of 2

E7150L







50 W Units 100 W Units A = 15.0" A = 15.0" B = 8.0" B = 8.0" C = 12.5" C = 12.5" D = 3.0" D = 4.5"

Features

Illumination: Illumination is provided by two 6 VDC or 12 VDC, 9 W, fully-adjustable Par 36 lamp heads.

Housing: Constructed of impact-resistant, UL 94 5 VA thermoplastic. Includes a low profile test switch and indicator lamp on the side of the unit. Off-white housing is standard.

Operating Temperature Range:

65°F (19°C) to 85°F (30°C)

Electronics: 120/277 VAC dual voltage input with surge-protected, solid-state charging circuitry provides for a reliable charging system. Charging system is compete with low voltage disconnect, AC lockout, brownout protection, AC indicator lamp and test switch.

Electrical Specifications: 0.11 A (120 VAC) 0.05 A (277 VAC)

Code Compliance

UL 924 listed. NFPA 101, NEC, BOCA, OSHA and IBC illumination standards.

Warranty

Three year full electronics warranty. One year full plus four year prorated battery warranty.

Job Information	Туре:
Job Name:	
Cat. No.:	
Notes:	



E7 Series

Commercial Grade Emergency Lighting

Page 2 of 2

Ordering Information

E7

Series Voltage/Wattage

E7 = E7 Series 150L = 6 V, 50 W Emergency 1100L = 6 V, 100 W Lighting Fixture 250L = 12 V, 50 W 2100L = 12 V, 100 W



Philips Lightolier

e: lol.webmaster@philips.com

t: (508) 679-8131

w: www.lightolier.com

E7 Series August 8, 2011

Job Information

Type:

Specifications are subject to change without notice.

© Koninklijke Philips Electronics N.V., 2011. All rights reserved.