


LDR Series


DIE CAST LED EXIT WITH REMOTE CAPABILITY

Page 1 of 2

LDRN1RW



Standard Canopy



Features

Illumination: Illumination of the exit stencil face is accomplished with long-lasting, high-output Light Emitting Diodes (LEDs). Hot spots and striations are eliminated by the internal "light chamber" especially designed around the high-performance LED array.

Housing: Two-piece die cast aluminum construction with NFPA-type field-selectable chevrons. Housing and stencil face castings are available with durable epoxy-based powder coat paint finishes. A brushed aluminum stencil face is also available. A positive latching exit stencil face provides secure closure yet is easily accessible for installation, maintenance and inspection. Universal knockouts located on canopy backplate allow for wall mounting directly to standard junction boxes.

Operating Temperature

Range: Standard Location
65°F (19°C) to 85°F (30°C)
Damp Location
50°F (10°C) to 104°F (40°C)

Electronics:

Emergency Operation - 120/277 VAC dual voltage input with surge-protected, solid-state circuitry provides for a reliable charging system. Charging system is complete with low voltage disconnect, AC lockout, brownout protection, AC indicator lamp and test switch.

Electrical Specifications:

Red:

10.4 W (120 VAC)

10.8 W (277 VAC)

Green:

9.8 W (120 VAC)

10.8 W (277 VAC)

Remote Capability:

Max. Remote Load - 10.8 W

Code Compliance

UL 924 and optional UL damp location listed. NFPA 101, NEC, BOCA, OSHA and IBC illumination standards.

Warranty

Three year full electronics warranty. One year full plus four year prorated battery warranty.

Job Information Type:

Job Name:

Cat. No.:

Notes:

PHILIPS

LIGHTOLIER

LDR Series

DIE CAST LED EXIT WITH REMOTE CAPABILITY

Page 2 of 2

Ordering Information

LDR	N				
Series	Battery	Stencil Faces	Letter Color	Stencil Face/Housing Color	Factory Installed Options
LDR = Die Cast Aluminum LED Exit with 10.8 W Remote Capability	N = Self-Powered	1 = Single 2 = Double	R = Red G = Green	A = Natural Brushed Aluminum Face w/ Black Housing B = Black Stencil Face w/ Black Housing N = Natural Brushed Aluminum Face w/ Natural Brushed Housing W = White Stencil Face w/ White Housing WA = Natural Brushed Aluminum Face w/ White Housing	DL = Damp Location Listing

Suggested Remote Lamp - ER Remote Unit



Lightolier's ER Remote unit is ideal for use with the LDR Series. Available in 6 V operation with your choice of single 6 W, 7.2 W or 9 W lamps, or dual 5.4 W lamps.

Ordering Information

Single Lamp
ER1T6WG = 6 V, 6 W
ER1T7WG = 6 V, 7.2 W
ER1T9WG = 6 V, 9 W

Dual Lamp
ER1MR10WG = 6 V, 5.4 W



Philips Lightolier
e: lol.webmaster@philips.com
t: (508) 679-8131
w: www.lightolier.com

LDR Series August 12, 2011

Specifications are subject to change without notice.
© Koninklijke Philips Electronics N.V., 2011. All rights reserved.

Job Information	Type:
------------------------	--------------