



MJ1 Series

Chicago Low-Profile Steel Unit

Page 1 of 2

MJ1126LH12W



Features

Illumination: High-output incandescent sealed beam lamps provide glare-free light distribution. 6 V, 12 W bi-pin halogen has an expected life of 100 hours.

Housing: Heavy duty steel cabinet is finished in neutral cream baked on powder paint providing scratch and corrosion resistance. All metal lamp housing and swivel assemblies in neutral cream color to match unit housing. Lamp heads are fully adjustable and feature lockable swivels.

Battery: Maintenance-free, sealed, lead calcium battery has an estimated service life of 5 years, and an operating temperature range of 68°F (20°C) to 86°F (30°C). Nickel cadmium batteries are optional.

Electronics: 120/277 VAC dual voltage input with surge-protected, solid-state circuitry. Fully automatic, temperature compensating, variable rate float charging system is complete with low voltage disconnect, AC lockout, brownout protection, AC indicator lamp, and test switch.

Code Compliance

All models are UL 924 listed and meet NFPA 101 Life Safety Code, NEC, OSHA and City of Chicago codes.

Warranty

Three year unit warranty (excludes lamps). One year full plus four year prorated battery warranty (lead calcium). Five year full plus five year prorated battery warranty (nickel cadmium).

Job Information Type:

Job Name:

Cat. No.:

Notes:

PHILIPS
LIGHTOLIER

MJ1 Series

Chicago Low-Profile Steel Unit

Page 2 of 2

Ordering Information

MJ1	1	24L	H12	W	
Series	Voltage	Battery Wattage	Lamp Type	Housing Color	Factory Installed Options
MJ1 = Chicago Steel Unit	1 = 6 V	24L = 26 W, Lead Calcium	H12 = Halogen 12 W	W = Neutral Cream	V = Voltmeter ¹ A = Ammeter ¹ LC = 3-Conductor Line Cord - 120 VAC B = Black Finish - Housing and Lamp Heads SX = Self-Diagnostic Circuit

Accessories (order as a separate item)

MJPG5 = Wire Guard
MJB1 = Mounting Bracket
MJS2 = Mounting Shelf
MJVERS = Vandal/Environmental Shield
MJVERS4X = Vandal/Environmental Shield with Gasket

Note

1) Unit has provisions for one meter option only.

Unit Battery Capacity

UNIT	DC VOLTAGE	LAMP WATTAGE	BATTERY WATTS TO 87 1/2 OF RATED VOLTAGE*			
			1 1/2 HRS	2 HRS	4 HRS	8 HRS
MJ1124LH12W	6	26	26	20	15	12

* Per NEC specifications.



Philips Lightolier
 e: lol.webmaster@philips.com
 t: (508) 679-8131
 w: www.lightolier.com

MJ1 Series May 30, 2012

Specifications are subject to change without notice.
 © Koninklijke Philips Electronics N.V., 2012. All rights reserved.

Job Information	Type:
------------------------	--------------