
CHICAGO STEEL TROFFER UNIT

Page 1 of 2

MJ3125LH12W





Features

Illumination: High-output incandescent lamps maximize illumination characteristics through a specially designed reflector and glass lens assembly that provides glarefree light distribution.

Housing: Heavy duty
steel cabinet is finished in
white baked-on powder
paint providing scratch and
corrosion resistance. All
metal lamp housing and swivel
assemblies in neutral cream
color to match unit housing.
Lamp heads are fully adjustable
and feature lockable swivels.

Battery: Maintenance-free, sealed, lead calcium battery has an estimated service life of 5 years, and an operating temperature range of 65°F (19°C) to 85°F (30°C). Nickel cadmium batteries are optional.

Electronics: 120/277 VAC dual voltage input with surge-protected, solid-state circuitry. Fully automatic, temperature compensating, variable rate float charging system is complete with low voltage disconnect, AC lockout, brownout protection, AC indicator lamp and test switch.

Code Compliance

All models are UL 924 listed and meet NFPA 101 Life Safety Code, NEC, OSHA and City of Chicago codes.

Warranty

Three year unit warranty (excludes lamps). One year full plus four year prorated battery warranty (lead calcium). Five year full plus five year prorated battery warranty (nickel cadmium).

ob Information	Туре:
ob Name:	
Cat. No.:	
Notes:	





CHICAGO STEEL TROFFER UNIT

Page 2 of 2

Ordering Information

MJ3

Series

1

1 = 6 V

Voltage

Battery Wattage

H12 Lamp Type W Housing Col

Housing Color

Factory Installed Options

MJ3 = Chicago Troffer Unit

6 V, Lead Calcium 25L = 25 W 50L = 50 W

26N = 26 W

6 V, Nickel Cadmium

H12 = Halogen 12 W

W = White

V = Voltmeter¹

A = Ammeter¹

A1H = Three Factory Installed Lamp Head (50 W units only)
A2H = Four Factory Installed Lamp Head (50 W units only)

B = Black Finish - Trim Plate and Lamp Heads

SP = Special Paint Finish - Specify Color

SX = Self-Diagnostic Circuit

Accessories (order as a separate item)

MJ908W08 = Matching Remote Head - Single (6 V, 12 W)
MJ909W08 = Matching Remote Head - Double (6 V, 12 W)

Note

1) Unit has provisions for one meter option only.



Philips Lightolier

e: lol.webmaster@philips.com

t: (508) 679-8131

w: www.lightolier.com

MJ3 Series September 19, 2011

Specifications are subject to change without notice.

© Koninklijke Philips Electronics N.V., 2011. All rights reserved.

Job Information

Type: