

CSA C22.2 No. 250.0 Certified
CSA Energy Efficiency Verified
C860 Compliant
Complies with all NRCan Exit Sign Energy Efficiency Requirements



SPECIFICATIONS:

- Product is available in two variations:
 - MI** Industrial is constructed with standard, zinc plated, Phillips drive hardware.
 - MV** Vandal is constructed with stainless steel, Phillips Security hardware.
- Both MI and MV come with a durable, clear, impact resistant polycarbonate cover that protects the fixture from vandalism and impact.
- Weatherproof option comes with silicone gasketing for the end plates and canopy (ceiling and end mount), neoprene gasket for cover plate, neoprene gasket for back wall mount. Gasketing provides protection from weather, dust and debris. **IP65** tested and approved.
- One piece, slim 1 1/4" depth, extruded aluminum housing. Standard finish is Duraplex II™ White Electrostatic Powder coat, optional colours available.
- Left and right directional chevrons custom machined to match each application or universal if specified.
- Exit and Sortie signs available in single or double face, letters are 6" high with 3/4" stroke.
- Mounting configuration can be Ceiling, Back Wall, End or Pendant. Mounting to be specified at time of order, not field adjustable.
- Custom wording signage is available upon request. Consult factory.
- Low energy consumption LED's are Dual 120/347VAC with 6/12/24VDC. 277VAC available upon request.
- Warranty on LED bar is 10 years (Parts only).

ELECTRICAL RATING:

Product	PRIMARY CIRCUIT			EMERGENCY CIRCUIT		
	AC Volts	Input Watts	Max. Amps	DC Volts	Input Watts	Max. Amps
EXIT	120	0.93	0.04	6	1.70	0.28
	347	1.02	0.04	12	1.42	0.12
				24	1.37	0.06
SORTIE	120	1.84	0.07	6	2.33	0.29
	347	2.00	0.07	12	1.68	0.14
				24	1.70	0.07

ORDERING GUIDE:

Example: **MVC1WUW-D**

--	--	--	--	--	--	--	--


Series ¹	Mounting	Faces	Sign Finish	Chevrons	Options	-	Input Volts
---------------------	----------	-------	-------------	----------	---------	---	-------------

MV : Vandal Exit MI : Industrial Exit MVS : Vandal Sortie MIS : Industrial Sortie MVC : Vandal Custom ¹ MIC : Industrial Custom ¹	C : Ceiling B : Back Wall E : End P : Pendant	1 : Single 2 : Double	W : White AA : Anodized Aluminum LB : Black SS : Silver SC : Special Colour ²	NC : No Chevron L : Left R : Right LR : Left & Right U : Universal	W : Weather Proof LED Bar ³ H : Hi Brightness LED Bar ³	D : 120/347V AC 4 : 277V AC
--	--	--	---	---	--	--

¹ Consult factory for custom wording requirements. Not applicable for 26.75" extrusion.
² Consult factory for special colour requirements & colour codes.
³ Not available in 277V AC.



***NOTE: POLYCARBONATE COVERS ARE SHOWN IN BLUE FOR CLARITY.**



PROJECT: _____

TYPE : _____

CATALOGUE NUMBER: _____