

CSA C22.2 No. 9.0 Certified
CSA Energy Efficiency Verified
C860 Compliant
Complies With All NRCan Exit Sign Energy Efficiency Requirements



SPECIFICATIONS:

- Housing is die formed extruded aluminum construction finished in Duraplex II™ White Electrostatic Powder coat, optional colours available.
- 6" high 3/4" stroke Exit or Sortie is silk screened onto 3/8" acrylic face. Face finish can be clear, white or specular. Legend can be single or double-faced.
- Low energy consumption LED's with universal self-detecting DC input voltage. Optical light guide provides uniform and bright letter illumination.
- Mounting configuration can be pendant mount, recessed ceiling (not shown), surface wall, ceiling or end mount.
- Dual tap AC input voltage 120/347 VAC. Self Detecting Emergency DC voltage 6 VDC to 24 VDC
- Complies to Safety Standard CSA 22.2 9.0 and Performance Standard CSA C860 (except double face SORTIE, all universal chevrons and specular face finishes).
- Warranty on LED bar is 10 years (Parts Only).

ELECTRICAL RATING:

Product	PRIMARY CIRCUIT			EMERGENCY CIRCUIT		
	AC Volts	Input Watts	Max. Amps	DC Volts	Input Watts	Max. Amps
EXIT	120	0.93	0.04	6	1.70	0.28
	347	1.02	0.04	12	1.42	0.12
				24	1.37	0.06
SORTIE	120	1.84	0.07	6	2.33	0.29
	347	2.00	0.07	12	1.68	0.14
				24	1.70	0.07

ORDERING GUIDE:

Example: **686SC1CWNC-D**



Series	Sign Type	Mounting	Faces	Face Finish	Trim Finish	Chevrons	Options	AC Voltage
686	Blank : EXIT S : SORTIE B : Bilingual	C : Ceiling B : Back Wall E : End P : Pendant R : Recessed Ceiling	1 : Single 2 : Double	W : White C : Clear M : Specular	W : White LB : Black SS : Silver SC : Special Colour ¹ BRA : Brushed Aluminum ²	U : Universal	H : High Brightness LED ³	D : 120/347V 4 : 277V

¹ Consult factory for your special colour requirements.
² Not available for Recessed Ceiling mounting.
³ Not available in 277V AC.

PROJECT: _____

TYPE: _____

CATALOGUE NUMBER: _____

