


OM8H200A23SPL

8" Horizontal A-Lamp Splay Lens Downlights

CAT. NO:

TYPE:

PROJECT:




PRODUCT INFORMATION

Applications

A special application fixture constructed of non ferrous metals for use in Magnetic Resonance Imaging hospital facilities. A soft edged, lensed downlight for use with economical A type incandescent lamps. Provides broad unifrom light distribution while concealing lamp image and maintaining good visual cut-off.

Specifications

- Mounting pan** - Precision die-formed 20 gauge galvanized steel mounting pan.
- Installation** - Mounting pan has pre-installed C-channel with vertical and horizontal adjustments. Yoke adjusts for proper positioning of lamp within reflector. Junction box and mounting brackets are accessible from below ceiling.
- Reflectors** - Precision spun .051 aluminum reflector, self flanged with clear specular Alzak finish. Reflector is screw mounted for positive attachment to socket assembly. Standard flat flange is painted white. Optional polished flange matching reflector finish available, add FF to catalog number.
- Splay Lens** - Spun aluminum regressed splay trim with white powder paint finish. Torsion spring mounting for ease of installation. Flat fresnel and prismatic lens for smooth, even distribution of light. Flat clear lens for enclosed applications.
- Socket** - Medium base 250V porcelain socket with nickel-plated copper screw shell and 200°C wire positions lamp at optical focal plane of reflector for maximum performance.
- Junction box** - Extra large 43.75-cubic inch 14 gauge aluminum with snap-on covers. Approved for through wiring with up to 8 #12 AWG conductors.
- Thermal protection** - A thermal protection device which meets all U.L. and NEC requirements is standard.
- U.L. Listed** - For use in wet locations in covered ceiling applications only. Approved for Through Branch Circuit Wiring. I.B.E.W. union made.



* Canadian Specifications may vary from these shown, consult Canadian Division.

8

CATALOG SYSTEM AND OPTIONS

EXAMPLE OF COMPLETE CATALOG NUMBER: OM8H200A23SPL-FL

OMEGA Aptr.	Lamp Position	Lamp (by others)	Reflector Option	Lens Type (required)	Frame Options**
OM8	H Horizontal	200 A23 150 A21	SPL Splay Lens (white) CSSPL Clear Specular Splay Lens BBSPL Black Baffle Splay Lens BKSP Splay Lens (Black)	FL Fresnel Lens PL Prismatic Lens CL Clear Lens	FB Flat Bar Hangers



FIVE YEAR
Warranty

OMEGA
LIGHTING

OMEGA LIGHTING:
776 South Green St., Tupelo, MS 38804
Phone 662.842.7212 FAX 662.841.5501

CANADIAN DIVISION:
189 Bullock Drive, Markham, Ontario, Canada L3P 1W4
Phone 905.294.9570 FAX 800.268.0003

omegalighting.com

OM8H200A23SPL-FL Photometric Data**Fresnel Lens with White Regressed Splay**

Report Number: ITL50732

Lamp: (1) 200W A23

Total Lumens: 3800


Fixture Efficiency: = 58.8%

IES File: ITL50732.IES

S/MH Ratio = 0.7, 0.5

Beam Angle: 39.03

LIGHTING PERFORMANCE DATA		
CEILING HEIGHT* (FT.)	INITIAL FOOTCANDLES	BEAM DIAMETER (FT.-IN.)
8	112.2	3-11
10	60.3	5-4
12	37.6	6-9
14	25.7	8-2
16	18.6	9-7

DISTRIBUTION CURVE**COEFFICIENTS OF UTILIZATION ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20								
RC	80		70		50			
RW	50	30	50	30	50	30		
0	69	69	68	68	65	65		
1	64	61	63	60	59	58		
2	57	56	56	55	55	53		
3	54	50	53	50	51	47		
4	48	46	48	45	46	44		
5	46	41	45	40	44	40		
6	42	39	41	38	40	38		
7	40	35	39	35	39	34		
8	36	33	36	33	35	33		
9	34	30	34	30	34	30		
10	33	28	33	28	32	28		

OM8H200A23SPL-PL Photometric Data**Prismatic Lens with White Regressed Splay**

Report Number: ITL50733

Lamp: (1) 200W A23

Total Lumens: 3800


Fixture Efficiency: = 61.3%

IES File: ITL50733.IES

S/MH Ratio = 1.1, 1.0

Beam Angle: 65.81

LIGHTING PERFORMANCE DATA		
CEILING HEIGHT* (FT.)	INITIAL FOOTCANDLES	BEAM DIAMETER (FT.-IN.)
8	61.5	7-1
10	33.1	9-8
12	20.6	12-3
14	14.1	14-11
16	10.2	17-6

DISTRIBUTION CURVE**COEFFICIENTS OF UTILIZATION ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20								
RC	80		70		50			
RW	50	30	50	30	50	30		
0	72	72	70	70	68	68		
1	67	65	65	64	63	61		
2	60	57	59	56	57	56		
3	56	52	55	52	53	51		
4	51	46	51	46	48	46		
5	46	42	46	42	46	41		
6	44	40	42	39	41	39		
7	40	36	40	35	40	35		
8	38	34	38	34	36	33		
9	35	32	34	30	34	30		
10	34	29	33	28	33	28		

*Readings at working plane, 2'6" above floor. Beam Angle and Diameter Cutoff at 50% of max.
Candlepower Coefficients used at effective reflectances of: 70% Ceiling, 50% Walls, 20% Floor

Additional photometric test files are available @ omegalighting.com
OMEGA
LIGHTING

OMEGA LIGHTING:
776 South Green St., Tupelo, MS 38804
Phone 662.842.7212 FAX 662.841.5501

CANADIAN DIVISION:
189 Bullock Drive, Markham, Ontario, Canada L3P 1W4
Phone 905.294.9570 FAX 800.268.0003