# **OM6150A21WW**

# 6" Reflector Wall Washers

CAT. NO:

**PROJECT:** TYPE:


# PRODUCT INFORMATION

#### **Applications**

A combination wall washer and downlight for use with economical A type incandescent lamps. Provides smooth, even light distribution on vertical surfaces in addition to supplementing general room illumination in areas such as lobbies, reception areas, schools, restaurants, hotels and offices.

- 1. **Mounting pan** Precision die-stamped 16 gauge galvanized steel mounting pan and yoke assembly. Accommodates ceiling materials up to  $1-3/8^n$  thick...
- 2. **Installation** Mounting pan has pre-installed C-channel with vertical and horizontal adjustments. Yoke adjusts for proper positioning of lamp within reflector. Junction box and mounting brackets are accessible from below ceiling.
- 3. Reflectors Precision spun .051 aluminum reflector, self flanged with clear specular Alzak finish. Reflector is screw mounted for positive attachment to socket assembly. Separate kicker reflector standard in semi-specular clear finish. Reflector rotates 360° for proper horizontal alignment. Standard flat flange is painted white. Optional polished flange matching reflector finish available, add FF to catalog number.
- 4. Socket Medium base 250V porcelain socket with nickel-plated copper screw shell and 200°C wire positions lamp at optical focal plane of reflector for maximum performance.
- 5. Junction box Extra large 43.75-cubic inch 16 gauge galvanized steel with snap-on covers. Approved for through wiring with up to 8 #12 AWG conductors.
- 6. **Thermal protection** A thermal protection device which meets all U.L. and NEC requirements is standard.
- 7. U.L. Listed For use in damp locations and approved for Through Branch Circuit Wiring. I.B.E.W. union made.





EXAMPLE OF COMPLETE CATALOG NUMBER: OM6150A21WW-CS

 Canadian Specifications may vary from these shown, consult Canadian Division.

## CATALOG SYSTEM AND OPTIONS

**OMEGA** Lamp Reflector Reflector Frame Aptr. (by others) (required) Finish\* Options\*1 OM<sub>6</sub> 100 A19 WW Wall Washer CS Clear Specular FB Flat Bar Hangers 150 A21 Clear Semi-Specular CSS **DWW** Double Wall Washer **CWW** Corner Wall Washer ΗZ GS Champagne Gold Specular

WT

PW



FIVE YEAR Warranty

(As suffix to color)

Wheat

Pewter Finish Flange

\*Consult factory for other reflector finishes.



# OM6150A21WW-CS

## Photometric Data

# Wall Washer with Clear Reflector

Source: Incandescent Lamp: 150W A21

Reflectances: 80% ceiling, 50% walls, 20% floor

Maintanance Factor: .10 IES File: F20952.IES

Distance from ceiling (ft)	2'6" from wall, 2'6" on center		2'6" from wall, 3' on center		3' from wall, 3' on center		3' from wall, 4' on center	
	Below Fixtures	Between Fixtures	Below Fixtures	Between Fixtures	Below Fixtures	Between Fixtures	Below Fixtures	Between Fixtures
1	5.3	4.9	4.9	4.2	2.9	3.1	2.8	2.1
2	41.3	41.6	36.0	33.3	23.4	22.6	21.5	13.3
3	41.2	42.8	34.5	35.8	31.3	32.4	24.3	23.3
4	32.6	34.0	27.2	28.7	27.7	28.4	20.7	21.6
5	25.7	26.1	21.5	22.4	22.7	23.7	17.0	18.2
6	21.1	20.7	17.9	17.7	18.9	19.1	14.1	15.1
7	17.7	17.5	15.2	14.8	16.3	15.9	12.3	12.5
8	15.5	15.6	13.5	13.3	14.5	14.2	11.2	11.0
9	13.8	14.0	12.2	12.1	13.1	12.9	10.2	10.0

# **OM6150A21DWW-CS**

## Photometric Data

## **Double Wall Washer with Clear Reflector**

Source: Incandescent Lamp: 150W A21

Reflectances: 80% ceiling, 50% walls, 20% floor

Maintanance Factor: .10 IES File: F20965.IES

Distance from ceiling (ft)	2'6" from wall, 2'6" on center		2'6" from wall, 3' on center		3' from wall, 3' on center		3' from wall, 4' on center	
	Below Fixtures	Between Fixtures	Below Fixtures	Between Fixtures	Below Fixtures	Between Fixtures	Below Fixtures	Between Fixtures
1	4.2	3.5	4.0	2.6	2.7	1.7	2.4	1.5
2	33.1	31.8	30.1	24.3	18.0	14.2	16.7	7.9
3	35.0	36.4	29.6	30.2	26.3	26.7	20.9	19.1
4	28.4	29.7	23.6	25.1	23.7	24.6	18.0	18.6
5	22.8	23.1	19.1	19.7	19.9	20.7	14.8	15.9
6	18.4	18.4	15.7	15.6	16.7	16.9	12.5	13.2
7	15.1	15.0	13.0	12.8	14.2	14.0	10.8	11.0
8	12.9	13.0	11.3	11.2	12.4	12.2	9.6	9.6
9	11.3	11.5	10.0	10.0	10.9	10.9	8.6	8.5



