

CATALOG NO. \_\_\_\_\_

TYPE NO. \_\_\_\_\_


JOB NAME \_\_\_\_\_

# FloodPak Series FPL



## ORDERING INFORMATION

Catalog Number: Example: FPL400MAL-8



\*Requires reduced outer jacketed lamp.  
HID units supplied with clear medium base lamp.

## ACCESSORIES

**FPLKNUCKLE** - Adjustable 2" Tenon Slipfitter.


**FPLARM** - Shoebox Arm. Converts FloodPak to pole-mount (minimum 4" square pole).

**FPLSHIELD** - Vandal Shield. Helps protect lens and lamp from breakage. Clear polycarbonate shield snaps in place over glass lens.

**FPLRPA** - Round pole adapter.

**FPL552** - Replacement Lens.

## TECHNICAL INFORMATION




UL Wet Location Listed.

## PRODUCT SPECIFICATIONS


- The FloodPak is a perfect blend of architectural design and performance.
- The FloodPak can be surface mounted in various positions. Use it as a cut-off wallpack or tip it up 22.5° for forward throw with semi-cut-off. Tip it up 45° for floodlighting, or turn it over and use it for indirect/accent lighting.
- The FloodPak can also be pole mounted or ground mounted using mounting accessories.
- Precision die cast aluminum construction. All exposed hardware is stainless steel.
- Duraplex II dark bronze polyester powder finish is standard but the FloodPak is available in a variety of designer colors.
- Hinged door frame with clear tempered glass lens.
- Multi-faceted reflection system provides uniform distribution.
- Injection molded triple finger silicone gasket.
- UL wet location listed for above or below horizontal aiming.
- Complete with a UL approved mounting box rated for 90°C supply wire with integral bubble level.
- Integral heat sink ensures cool operation.
- Meets IESNA cut-off requirements.
- Contractor Friendly design with integral cable permitting easy, hands free wiring.

# FloodPak Series FPL


## PHOTOMETRICS



FPL400MAL-8 @ 0°



FPL400MAL-8 @ 22.5°



FPL400MAL-8 @ 45°

### FOOTCANDLE CORRECTION

Multiply the following factors times the footcandle values for changes in mounting height.

To Change from 20'


New Hght.	15'	20'	25'	30'
Factor	1.78	1.0	.64	

.44

### LAMP AND WATT CONVERSIONS

Lamp	250W MH	250W HPS	400W HPS	400W MH
Multiplier	.57	.79	1.39	1.0

## MOUNTING OPTIONS



© 2013 Koninklijke Philips Electronics N.V. All rights reserved.  
Specifications are subject to change without notice.  
[www.philips.com/luminaires](http://www.philips.com/luminaires)

05/13

Philips Lighting Company  
200 Franklin Square Drive  
Somerset, NJ 08873  
Phone: 855-486-2216

Philips Lighting Company  
281 Hillmount Road  
Markham ON, Canada L6C 2S3  
Phone: 800-668-9008