

CATALOG NO. _____

TYPE NO. _____ JOB NAME _____

Survi'VR S Series Vandal-Resistant Luminaire (8' Linear Fluorescent)




ORDERING INFORMATION

Catalog Number: Example: SATO2321K4YBF

S	AT							
SERIES	STYLE	LENS	LAMPS	WATTAGE	VOLTAGE	BALLAST SOURCE	COLOR	OPTIONS
S Survi'VR Series Vandal Resistant	AT -Aluminum Tandem	O -Opal Poly C -Clear Poly	2 (per cross section)	28 -28W T5 32 -32W T8 54 -54W T5HO	1 -120V 7 -277V B -120-277V	N8Y -T5 K4Y -T8 S4Y -T5HO	B -Black W -White P -Bronze	2C -2 Circuit 3C -3 Circuit F -Fused RB -Row Beginning RM -Row Middle RE -Row End PC -Photo Control Battery Back-Up Consult Factory

PHOTOMETRIC DATA

Mounting Height = 12 ft.
Gridscale = 12 ft. per increment




SATO432K4YW
8' Linear - Ceiling Mount
4-32w T8 fluorescent

Horizontal Footcandles
Lumen/Lamp = 2,850
Light Loss Factor = 1.00

.1 FT-C	.2 FT-C	.5 FT-C	1 FT-C	2 FT-C	5 FT-C
---------	---------	---------	--------	--------	--------

TECHNICAL INFORMATION



PRODUCT SPECIFICATIONS

- Marine grade extruded aluminum side rails and back rails
- Precision die-cast, marine-grade aluminum
- Extruded, UV-stabilized polycarbonate lens available in prismatic opal or prismatic clear styles
- Electronic high-frequency with voltage sensing capability in T5, T5HO and T8 lamping
- Precision snap-type, spring-loaded sockets
- High-reflectance white pan reflector system
- Duraplex II polyester powder finish
- "LifeLyte" limited lifetime warranty
- UL listed for wet locations

