

CATALOG NO. \_\_\_\_\_

TYPE NO. \_\_\_\_\_

JOB NAME \_\_\_\_\_

## Xpressives Series



### Medium and Large Shallow Fluted

(HID, Incandescent and Compact Fluorescent)



- Ideal for restaurants, taverns or nightclubs, food courts, atriums or plazas, malls, retail outlets, stores, athletic clubs and facilities, theatres, arenas, stadiums and amusement parks.
  - Spun aluminum shade standard.
  - Precision die-cast aluminum electrical cap attaches to shade via keyhole slots. Cap locks into place using set screw, and two-piece shade/cap assembly attaches to cord or pipe.
  - Corrosion-resistant Duraplex II polyester powder-coated finish with optional designer finishes available.
  - Remote or surface ballast mounting with a porcelain 4KV pulse rated socket. Most fixtures furnished with 96" leads with a maximum distance for electronic HID is 5' from ballast to lamp.
  - Corrosion-resistant Duraplex II white polyester powder-coated reflector finish standard except for metallic textured finishes having the same both sides.
  - 1/2" or 3/4" aluminum stem/goosenecks are schedule 40 with no exposed threads.
  - Straight or coil white cord available in 18/3 SJTOW.
  - Wall plate/ballast box made from die cast aluminum.
  - CSA listed for wet locations.
- See page 2 for ordering information  
- See arm specification sheet for arm styles  
- See mounting specification sheet for mounting components

## TECHNICAL INFORMATION
















® Listed for wet locations

# Xpressives Series Medium and Large Shallow Fluted

## ORDERING INFORMATION

Catalog Number: Example: X3FSW3C085HGRGYU1P

Series	Style	Ballast	Mounting	Wattage	Source	Texture	Color	Texture	Color	Color Combo	Voltage	Options
												
X=	2F=	R=	W1A	050	P- Electronic	W-	G-	W-	G-	Q-	1-	G-
Xpressives	Shallow	Remote	W1B	070	Pulse Start	Wrinkle	Green	Wrinkle	Green	Combo	120	Vaportite
	Fluted	S=	W1C	100	Metal Halide¹		B-		B-	SCPM	8-	Globe
	(Medium)	Surface	W1E	150			Black		Black	T-	120-277	Photo
	3F=						W-		W-	Combo		Control
	Shallow		W3A	050	M- Magnetic		White		White	S-CPM		Control
	Fluted		W3B	070	Pulse Start		P-		P-	U-		T-
	(Large)		W3C	100	Metal Halide*		Bronze		Bronze	Combo		Thru-
			W3D	150	*Remote only					SC-PM		Wiring
			W3E	175						V-		B-
						F- Flat	B-	F- Flat	B-	Combo		G & T
			SWF	075	I- Incandescent		Black		Black	SCP-M		options
			SWG	100	(use with 6" plat only)		P-		P-	W-		combined
				200			Bronze		Bronze	Combo		C-
				300³		G- High Gloss	G-	G- High Gloss	G-	SP-CM		G & P
			C11				Green		Green	X-		options
			C12	026	H- Electronic		B-		B-	Combo		combined
			C13	032	Compact		Black		Black	SPM-C		D-
			C14	042	Fluorescent		W-		W-	Y-		T & P
			C31	060³	(not for use w/ any cord mounting units)		White		White	Combo		options
			C32	085³			Y-		Y-	SM-CP		combined
			C33				Yellow		Yellow	Z-		E-
			C34				U-		U-	Combo		G & T & P options combined
					(60w and 85w compact fluorescent requires remote ballast)		Blue		Blue	SMC-P		
			SC5				R-		R-			
			SC0¹				Red		Red	Cord		
			SC5			M- Metallic	C-	M- Metallic	C-	Q-		
			SC0¹				Copper		Copper	Combo		
			CC5				S-		S-	SCM		
			CW5				Silver		Silver	T-		
							G-		G-	Combo		
							Galvanite		Galvanite	S-CM		
			PF1							U-		
			PF2							Combo		
			PF3							SC-M		
			PF4			T- Textured	S-	T- Textured	S-	Y-		
			PF5				Silver		Silver	Combo		
			PG1							SM-C		
			PG2									
			PG3									
			PG4									
			PG5									

**Combo Key**  
S- Shade  
C- Cap  
P- Pipe  
M- Mounting

**(Note:** "T" only with the ballast box and not for use with INC fixtures)  
Medium shades have 100w max for INC and large shades have 200w max for INC. Also, 42w CFL cannot use globe.

## MOUNTING DEFINITIONS

<b>W1A</b> = Wall 1/2" Stem Style GNW1A <sup>2</sup>	<b>C11</b> = Ceiling 1/2" 1 ft Stem Style GNC11 <sup>2</sup>	<b>PF1</b> = Post Top Pole (1 FIXT w/ GNP3F)
<b>W1B</b> = Wall 1/2" Stem Style GNW1B <sup>2</sup>	<b>C12</b> = Ceiling 1/2" 2 ft Stem Style GNC12 <sup>2</sup>	<b>PF2</b> = Post Top Pole (2 @ 90 w/ GNP3F)
<b>W1C</b> = Wall 1/2" Stem Style GNW1C <sup>2</sup>	<b>C13</b> = Ceiling 1/2" 3 ft Stem Style GNC13 <sup>2</sup>	<b>PF3</b> = Post Top Pole (3 @ 90 w/ GNP3F)
<b>W1E</b> = Wall 1/2" Stem Style GNW1E <sup>2</sup>	<b>C14</b> = Ceiling 1/2" 4 ft Stem Style GNC14 <sup>2</sup>	<b>PF4</b> = Post Top Pole (4 @ 90 w/ GNP3F)
		<b>PF5</b> = Post Top Pole (2 @ 180 w/ GNP3F)
<b>W3A</b> = Wall 3/4" Stem Style GNW3A	<b>C31</b> = Ceiling 3/4" 1 ft Stem Style GNC31	<b>PG1</b> = Post Top Pole (1 FIXT w/ GNP3G)
<b>W3B</b> = Wall 3/4" Stem Style GNW3B	<b>C32</b> = Ceiling 3/4" 2 ft Stem Style GNC32	<b>PG2</b> = Post Top Pole (2 @ 90 w/ GNP3G)
<b>W3C</b> = Wall 3/4" Stem Style GNW3C	<b>C33</b> = Ceiling 3/4" 3 ft Stem Style GNC33	<b>PG3</b> = Post Top Pole (3 @ 90 w/ GNP3G)
<b>W3D</b> = Wall 3/4" Stem Style GNW3D	<b>C34</b> = Ceiling 3/4" 4 ft Stem Style GNC34	<b>PG4</b> = Post Top Pole (4 @ 90 w/ GNP3G)
<b>W3E</b> = Wall 3/4" Stem Style GNW3E		<b>PG5</b> = Post Top Pole (2 @ 180 w/ GNP3G)
<b>SWF</b> = 3/4" Stem Adapter w/ GNP3F	<b>SC5</b> = Straight Cord 5 ft	
<b>SWG</b> = 3/4" Stem Adapter w/ GNP3G	<b>SC0</b> = Straight Cord 10 ft <sup>1</sup>	
	<b>SA5</b> = Straight Cord w/ aircraft 5 ft	
	<b>SA0</b> = Straight Cord w/ aircraft 10 ft <sup>1</sup>	
	<b>CC5</b> = Coil + Cord 5 ft	
	<b>CW5</b> = Cord Wet Location 5 ft	

# Xpressives Series Medium and Large Shallow Fluted

## ACCESSORIES

### Trim Rings



**TR2XX** for use with medium shades

**TR3XX** for use with large shades

Note: Available in all color/texture combinations

### Cast Guards




Guard only. Available only with "G" option

**V131XX** 3-1/2" twist on/off cast aluminum guard

**V132XX** 4-3/8" twist on/off cast aluminum guard

Note: Available in all color/texture combinations

### Aircraft Cable Support



**ACS1XX** 1/2" Aircraft Cable Support

**ACS3XX** 3/4" Aircraft Cable Support

Note: Brackets available in all color/texture combinations


### Fusing

**FS** Consult factory for availability

Note: Fusing can only be used in surface mounting


# Xpressives Series Medium and Large Shallow Fluted

## PHOTOMETRIC DATA




**KALEIDOSHADE 2**  
**MEDIUM SHALLOW FLUTED**  
**PHILIPS 150 WATT A-21 INC LAMP @ #1 POSITION**  
**IES Test # K2F150IG**

Total Rated Lamp Lumens	2850
Total Luminaire Efficiency	94.7 %
CIE Type	Direct
Spacing Criteria (0-180)	1.32
Spacing Criteria (90-270)	1.32
Spacing Criteria (Diagonal)	1.50
Basic Luminous Shape	Circular w/ Sides
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	1.33 ft (Diameter)
Luminous Height	0.46 ft



**KALEIDOSHADE 2**  
**LARGE SHALLOW FLUTE REFLECTOR**  
**PHILIPS 200 WATT INC PS-30 COATED LAMP**  
**IES Test # K3F200IG**

Total Rated Lamp Lumens	3710
Total Luminaire Efficiency	91.1 %
CIE Type	Direct
Spacing Criteria (0-180)	1.36
Spacing Criteria (90-270)	1.36
Spacing Criteria (Diagonal)	1.58
Basic Luminous Shape	Vertical Rectangle
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	1.66 ft
Luminous Height	1.04 ft



**KALEIDOSHADE 2**  
**LARGE SHALLOW FLUTED REFLECTOR,**  
**PHILIPS 300 WATT INC COATED PS-35 LAMP**  
**IES Test # K3F300IG**

Total Rated Lamp Lumens	5150
Total Luminaire Efficiency	87.1 %
CIE Type	Direct
Spacing Criteria (0-180)	1.32
Spacing Criteria (90-270)	1.32
Spacing Criteria (Diagonal)	1.50
Basic Luminous Shape	Vertical Rectangle
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	1.66 ft
Luminous Height	1.04 ft



© 2013 Koninklijke Philips N.V. (Royal Philips). All rights reserved.  
Specifications are subject to change without notice.  
[www.philips.com/luminaires](http://www.philips.com/luminaires)

05/13

Philips Lighting Company  
200 Franklin Square Drive  
Somerset, NJ 08873  
Phone: 855-486-2216

Philips Lighting Company  
281 Hillmount Road  
Markham ON, Canada L6C 2S3  
Phone: 800-668-9008